

Ground Set Cone Tapered Aluminum (6063-T6) Flagpoles



GENERAL INFORMATION

Our cone tapered ground set aluminum flagpoles are precision fabricated from new, **6063-T6** tubing utilizing the industry's most sophisticated manufacturing processes. The conical portion tapers approximately 1" in every 5-1/2 feet. Poles with overall lengths of less than 38'6" are shipped in one piece. Longer lengths are shipped in sections and will be factory fitted with a self-aligning sleeve which requires no field welding. Upon proper assembly a hair-line joint will occur. All poles are double spiral wrapped with protective paper and shipped in a hard fiber tube. All foundation dimensions listed in this catalog are intended for general guidelines only in good, firm, dry soil. It is recommended to consult an engineer for specific foundation dimensions suited to your exact location.

STANDARD FINISHES

All flagpole shafts are highly polished with fine grain aluminum oxide cloth resulting in a high quality, deep satin lustre finish. This finish represents the ultimate in architectural finishes for aluminum flagpoles. The elegant, soft sheen remains maintenance free. The following anodized finishes are available as standard colors. *Note: For bronze, dark bronze #313 is supplied unless otherwise specified.*



SATIN




CLEAR



BRONZE #311
(LIGHT)



BRONZE #312
(MEDIUM)



BRONZE #313
(DARK)



BLACK
(#335)

CUSTOM FINISHES

We also offer alternate finishes & custom paint colors which may suit particular job conditions better. Contact us for a prompt quotation.

“WARNING”

WARNING: The flagpole shaft will stain if allowed to remain in contact with wet or damp wrappings. If there is any sign that the shaft or its shipping tube has come in contact with water during shipment, remove it from the tube and unwrap immediately. If the shaft is to be stored outdoors, it must be stored unwrapped, out of the tube, and off the ground. If the shaft is to be stored indoors, it may be left in the wrappings and the tube, provided that it shows no sign of having been exposed to moisture and that it will not be exposed to moisture during storage.

“WARNING” - The flagpole shaft will stain if allowed to remain in contact with wet or damp wrappings. If there is any sign that the shaft or its shipping tube has come in contact with water during shipment, remove it from the tube and unwrap immediately. If the shaft is to be stored outdoors, it must be stored unwrapped, out of the tube, and off the ground. If the shaft is to be stored indoors, it may be left in the wrappings and the tube, provided that it shows no sign of having been exposed to moisture and that it will not be exposed to moisture during storage.

USE NO FORKS CAUTION!!!!

EXTREME CARE MUST BE EXERCISED WHEN INSTALLING AND FLAGPOLES NEAR OVERHEAD POWER LINES, OR WHEN DIGGING IN THE VICINITY OF BURIED CABLE.

“CAUTION” - Extreme care must be exercised when installing flagpoles near overhead power lines or when digging in the vicinity of buried cable or piping. Contact your local authorities before any digging.